





Item#	Model #	Description	Photo
1	70-D360-V1-A10-00	<p>DPX360 unit (Industrial Optical Instrument), for the complete analysis of Multi-Fiber and Single-Fiber optical connectors, via interferometry and microscopy functionalities, including:</p> <ul style="list-style-type: none"> - 1 measurement plugin BLINK-INTERFEROMETRY, - 1 measurement plugin BLINK-INSPECTION-MT, 1 BLINK-INSPECTION-SF, including DEEP LEARNING feature, - "Generation 3" controller board for faster and more accurate scans, - 1 USB key, (Installation & Standard user manual), - 1 Set of Electronic Board PCI Express x4 USB 3.0, 4 ports with Sata power cable, - 1 carrying case, 1 Power supply 12v, 1 USB 3.0 cable, 1 Screwdriver (2.5 x 75) 	
2	30-FL-004136	<p>Flange MT Female, MT-12/24 ferrules and MPO connectors, with tapered pins (2 long) (12 fibers per row, 1 to 6 rows)</p> <p>注释: for US CONEC MMC Sr: measurement of female MMC Sr connector is possible using the flange 30-FL-004136 and the adapter 30-AD-004525, only if the female pin spacer is not mounted on the connector.</p>	
3	30-FL-004137	<p>Flange MT Female, MT-16/32 ferrules and MPO connectors, with tapered pins (2 long) (16 fibers per row, 1 to 6 rows)</p> <p>注释: for US CONEC MMC Sr: measurement of female MMC Sr connector is possible using the flange 30-FL-004137 and the adapter 30-AD-004525, only if the female pin spacer is not mounted on the connector.</p>	

Item#	Model #	Description	Photo
4	30-FL-004138	Flange MT Male, without pins, MT-12/24 ferrules and MPO connectors (12 fibers per row, 1 to 6 rows)	
5	30-FL-004139	Flange MT Male, without pins, MT-16/32 ferrules and MPO connectors (16 fibers per row, 1 to 6 rows)	
6	30-FL-004452	Flange 2.50mm, manual, with Hard Metal sleeve	
7	30-FL-004453	Flange 1.25mm, manual, with Hard Metal sleeve	
8	30-AD-004140	Adapter, PC and APC, MT bare ferrule MT-12/24 and MT-16/32 ferrules	
9	30-AD-004141	Adapter, PC and APC, MPO with housing, MPO-12/24 connectors, double key	
10	30-AD-004142	Adapter, PC and APC, MPO with housing, MPO-16/32 connectors, double key	

Item#	Model #	Description	Photo
11	30-AD-004524	<p>Adapter, specific for US CONEC TMT ferrules (TMT-16, TMT-12, TMT-2x12) and MMC Jr connectors (MMC-16, MMC-12, MMC-2x12)</p>	
12	30-AD-004525	<p>Adapter, specific for US CONEC MT-16 MMC Sr connectors</p> <p>Note: - For MMC (MT-16): measurement of female MMC Sr connector is possible using the flange 30-FL-004137 and the adapter 30-AD-004525, only if the female pin spacer is not mounted on the connector.</p> <p>- the minimum requirement for the Daisi-MT interferometer is version V3, and for the Daffi-MT: Daffi MT 16</p> <p>Note: - For MMC (MT-12, MT-2x12): measurement of female MMC Sr connector is possible using the flange 30-FL-004136 and the adapter 30-AD-004525, only if the female pin spacer is not mounted on the connector.</p>	